

B200

AC Contour Probe

The B200 Contour Probe is a rugged high performance instrument designed for Magnetic Particle inspection to accepted Nondestructive testing standards.

Parker Contour Probes are designed with flexible legs that allow the field to be "focused" at a precise area of inspection. Components are protected by a reinforced glass-filled nylon housing. Model B200 and B200S produce a strong constant AC field.

Plastic carry cases (PL-Case) and Test Kits (PL-A Kit & A Kit) are available. Standard test kits include 1 lb. each of Red & Gray powder, PB1 powder blower, and carrying case.

Features

- High-impact, glass-filled nylon housing
- AC Only
- Dual coil design for reduction of heat to the operators hand
- Ergonomic handle for ease of use over long periods of time
- Plastic actuator for consistent activation of the switch
- One year repair/replacement guarantee
- Exceeds ASTM lifting standards

Standards Compliance

- IP51
- ASME Section V, Article 7
- ASTM E709
- ASTM E1444
- ASTM E3024
- EN ISO 9934-3 (230V Only)
- CE (Optional 230V Only)



Applications

Defect location: Surface

Ideal for:

- Field Testing
- Spot Inspections
- In-service Inspections
- Demanding Environments
- Welding Inspections

Defect Examples:

- Inclusions
- Seams
- Shrink cracks
- Tears
- Laps
- Welding slags
- Grinding cracks
- Quenching cracks
- Fatigue cracks

April 2020 Page **1** of **2**



Product Properties

| Weight | 7 lbs. (3.18 kg) |
|----------------------------|--|
| Leg Span | 0 – 12 in (0 – 304.8 mm) |
| Cord Length | 10 ft. (3.048 m) |
| Duty Cycle | 50% |
| Electrical Requirements | 115VAC - 50/60 Hz : 3 Amps 230VAC - 50/60 Hz : 2 Amps |

Use Recommendations

| NDT Method | Magnetic Particle Testing |
|-------------|-----------------------------|
| Recommended | Weight Lift Test Bar – TB10 |
| Accessories | Yoke Light – Y200 |

Part Numbers

B200 - 115VAC

B200S - 230VAC

April 2020 Page 2 of 2